



MZG-2088

Z-Wave Home Automation Control Gateway



HOME AUTOMATION CONFIGURATIONS

- Energy and cost saving by automatically / manually turning off those devices not in use
- Provides pre-defined scene modes such as wake up, sleep and more
- Control lights based on time and occupancy
- Control thermostats based on schedules and occupancy
- Ensure entry doors are closed and locked remotely
- Completely power down audio and video equipment, and other appliances at night
- Real-time image monitoring of community public cameras
- Remotely control your shades and blinds
- 24-hour emergency monitoring

EASY INSTALLATION & MANAGEMENT

- App and control pad alerts for any situation

Specifications

Model	MZG-2088
Hardware Platform	
Wi-Fi	IEEE 802.11b/g/n
LED Indicators	PWR
Buttons	1 x reset button
LAN Interface	1 x 10/100Mbps Ethernet port
Enclosure	Plastic
Network and Configuration	
Network Standard	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX
Z-Wave Frequency	Europe: 868.42MHz America: 908.42MHz
HA Functions	Sense Control/Door Lock/ControlSensor/Trigger/Schedule/ Setting/Supports Mobile Phone Push Notification/ Lighting control/User account Management (admin and normal user)/ Support remote update/software/Support 30 Z- Wave notes
Peripherals and Devices	
Power Requirements	12V DC, 1A
Operating Temperature	0 ~ 45 degrees C
Operating Humidity	10 ~ 90% (non-condensing)
Weight	300g
Dimensions (W x D x H)	137 x 101 x 30 mm (W*H*D)
Emission	CE, FCC

Ordering Information

MZG-2088	Z-wave Home Automation Control Gateway
----------	--